

# Specifications for SnoBar Snow Retention System for Metal Roofs

## PART 1 – GENERAL

### 1.1 SUMMARY:

- A. WORK INCLUDES:
  - 1. Snow retention system that clamps directly to the standing seams without penetrating the roof system. Screw-down mounted ColorBrackets are used for mechanically fastened roofs.
  - 2. Coordinate with the installation of the metal roofing system to assure the proper fastening of the metal roof to the substructure.
  - 3. Provide all necessary components: Clamps/ColorBrackets, Bars, Set Screws, Tek Screws, End Caps and optional IceStoppers.
- B. RELATED SECTIONS:
  - 1. Master Format™ 2004 Section 07 41 13: Preformed Metal Roofing
  - 2. Master Format™ 2004 Section 07 60 00: Flashing and Sheet Metal
  - 3. Master Format™ 2004 Section 07 40 00: Metal Roof Panels
  - 4. Master Format™ 2004 Section 07 61 01: Sheet Metal Roofing

### 1.2 SYSTEM DESCRIPTION:

- A. COMPONENTS:
  - 1. SnoBar System consisting of 12 Ga. stainless steel, one piece, top loading, non-penetrating clamps and 16 Ga. Galvanized Steel or Stainless Steel 1" Square Bars.
  - 2. Set screws to be "cup tipped", Stainless Steel, 3/8" diameter, torqued to 90 in/lbs.
  - 3. Bar to be attached to clamp with two (2) corrosion protected #10 tek screws. Screw-down mounted ColorBrackets are used for mechanically fastened roofs.
  - 4. Plastic end caps to be installed in each end of bar.
  - 5. *Optional:* Aluminum "Ice Stopper" centered on panel and mounted perpendicular to roof panel to prevent sliding ice. Use over pedestrian areas or on areas needing additional protection.
- B. DESIGN REQUIREMENTS:
  - 1. Clamps must be used at every roof seam.
  - 2. Snow retention system should have a minimum performance of 500# per linear foot of bar without deflection and 500# per clamp without significantly damaging the roof panel.
  - 3. Based on snow load, climatic conditions, length of roof panel and width of panel; multiple rows of SnoBar may be needed.
  - 4. Provides attachment without voiding roof panel warranty.
- C. METAL ROOFING AND SUBSTRATE CRITERIA:
  - 1. Metal roofing must be a minimum of 24 Ga. Steel.
  - 2. All loads incurred by the SnoBar will be transferred to the panels; therefore proper panel attachment to substrate/structure is necessary to prevent roof panels from sliding under snow load. It is important to design new structures or assess the existing structure to make sure it can withstand retained snow loads. (*Architect Note: Add this requirement to Metal Roofing Section*)

1.3 SUBMITTAL: – Submit Manufacturer's specifications, standard detail drawings and installation instructions.

1.4 QUALITY ASSURANCE: – Installer to be experienced in the installation of metal roofing and snow retention systems for a period of not less than 5 years in the area of the project.

1.5 DELIVERY/STORAGE/HANDLING: – Inspect material upon delivery and order replacements for any missing or defective items. Keep material dry, covered and off the ground until installed.

## PART 2 – PRODUCTS

### 2.1 MANUFACTURER:

Action Manufacturing, LLC  
Exclusively Distributed by  
IceBlox, Inc. d.b.a.  
Snoblox-Snojax

**Phone:**  
(800) 766-5291  
(717) 737-4398

**Fax:**  
(800) 634-7906  
(717) 697-6141

**Online:**  
www.snojax.com  
support@snojax.com

**Warehouse:**  
671 Willow Street  
Lemoyne, PA 17043

### 2.2 MATERIALS:

- A. Clamps: 12 Ga. one-piece stainless steel clamps with 2 "cup tipped" stainless steel set screws used at every roof seam.
- B. Bars: Specify a 16 Ga. Galvanized Steel Bar or 16 Ga. Stainless Steel Bar.

### 2.3 FINISH: – (pick one of the following finishes)

- A. Powder Coat – Color to match or be similar to metal roof or as selected by architect
- B. Unpainted Mill Finish

## PART 3 – EXECUTION:

### 3.1 EXAMINATION:

- A. Substrate: Inspect roof system to be properly attached and installed to withstand additional loadings incurred. Notify General Contractor of any deficiencies before installing SnoBar

### 3.2 INSTALLATION:

- A. Comply with architectural drawings for location and with Manufacturer's instructions for assembly, installation and erection.
- B. Clamps must be used at every roof seam in straight rows.
- C. All Set Screws torqued to 90 in/lbs. and rechecked annually.
- D. Optional mechanically fastened Colorbracket attachment available.
- E. Refer to manufacturer's installation instructions <http://www.SnobarColorBar.com/installation-instructions/>.

### 3.3 WARRANTY

- A. SnoBar systems shall include free limited lifetime warranty on parts and finish for all systems following manufacturer's spacing/ installation recommendations.