

# IceStoppers



1 (800) 766-5291  
(717)737-4398

[www.SNOBLOX-SNOJAX.com](http://www.SNOBLOX-SNOJAX.com)



**XXL**  
FITS SEAM HEIGHTS  
3.25"-3.75"

**XL**  
FITS SEAM HEIGHTS  
2.75"-3.25"

**L**  
FITS SEAM HEIGHTS  
2.25"-2.75"

**M**  
FITS SEAM HEIGHTS  
1.75"-2.25"

**S**  
FITS SEAM HEIGHTS  
1.00"-1.50"



IceStoppers prevent snow and ice from sliding under the SnoBar and ColorBar. They are mounted to the back side of the bar with 2 included self-drilling tek screws that are hidden from view once installed. The 90-degree angled foot adds stability and prevents the IceStoppers from bending under the bar. Because they are mechanically mounted, they can't slide side to side or allow snow to ramp over the bar, like some other competing products. IceStoppers are highly recommended, especially over pedestrian areas and walkways. They can easily be added to new SnoBar and ColorBar systems or retrofitted onto existing systems.

12" to 16" wide standing seam panels typically have one IceStopper installed in the center of the panel valley. 18" to 24" standing seam panels require two IceStoppers proportionally spaced in each panel valley. Wider panels, such as 36" to 42" standing seam panels, require at least three IceStoppers proportionally spaced in each panel valley.